



HRP4

Asset GPS Tracker

a GPS + LBS positioning

Allow the location to be pinpointed in real time or periodically

II Intelligent power management

Reduce inefficient power consumption when the device stays idle

D IPX5 water proof

Water-resistant case to ensure stable operation in tough environment

● 10000mAh battery

LED display for you to view battery status

ti Voice monitoring

Listen to the surroundings by sending SMScommand

m Strong magnet

Strong magnetic cover allowing for flexible mounting on vehicles or assets

Tamper alert

Be notified of any removal from original installation

Cover dismantlement alarm

Alarms triggered if SIM changed or device tuned on/off illegally

Application



Fleet Management



Vehicle rental



Logistics

GSM Specification

GSM frequency	850/900/1800/1900MHz
GPRS	Class 12, TCP/IP
Memory	32+32Mb
Phase error	RMSPE<5, PPE<20
Max output	GSM850/GSM900:33±3dBm GSM 1800/GSM 1900:30±3dBm
Max frequency error	±0.1ppm
Receive sensitivity	Class 1 RBER 2%(-102dBm)

GPS Specification

Chipset	High sensitivity GPS chips
Frequency	GPS L1, 1575.42MHz
Channel	66
Location accuracy	<10 meters
Tracking sensitivity	-165dBm
Acquisition sensitivity	-148dBm
TTFF (open sky)	Avg:hot start 11 sec Avg. cold starts 32sec

Others

Switch	1 for base falling detection; 1 for inner dis-assembly detection; 1 for power control
Button	1xpower
GSM/GPS antenna	Built-in quad band GSM antenna, GPS ceramic antenna and WiFi antenna
LED indicator	Red: working status; Green (4): battery
Working voltage/current	3.7V/60mA
Tracking mode	30 days(drive for 2 hours per day)
Operating temperature	-20 °C- +70 °C
Battery	10000mAh/3.7V industrial grade lithium polymer battery
Charger	5VDC /2A
Charging hour	8 hours
Device weight	285g
Device dimension	108.0 x 61.0x 30.0mm

HRP4

Contact

Danie Booyens
Hawk Risk Protection (PTY) Limited
7 Weber Close, Boksburg, Johannesburg, South Africa
Tel: +2771 2126715
Web: www.dcl-hawktek.co.za
Email: danie@dcl-hawktek.co.za